INTRODUCTION

Urethane Technologies, Inc. primarily manufactures surface floatation buoys using the following combination of materials:

A metallic frame or through rod is used with the body of the buoy made of a cross-linked, closed cell polyethylene foam protected by a tough Seathane® polyurethane skin. Crosslinked polyethylene foam has a much lower moisture vapor transmission rate than most other floatation foams and; as such, will not absorb a significant amount of water during long term immersion. Seathane® is our proprietary polyurethane with a 500% elongation and a 4,500 psi tensile strength. On larger buoys the Seathane® skin is woven fabric reinforced for added cut resistance. Where very rough physical abuse is anticipated; Spectra® woven is used for the reinforcement. Spectra® is a space age fiber with a 375,000 lb./sq. inch tensile strength.

We are not limited to manufacturing only the items depicted in this catalog. Approximately 35% of our production is in custom designed buoys that are not shown herein. Urethane Technologies also manufactures the following:

- Sub-sea riser buoys
- Ship fendering
- Dock fendering
- Pontoons
- Bridge camels
- Dredge pipe camels
- Push boat bow pads
- Equipment barges
- Instrument buoys
- Floatation collars
- Custom cast polyurethane items
- Dive tank racks
- Steel buoys
- Polyurethane drilling deck pads
- Sport fishing teasers and large trolling lures
- Polyurethane casting resins

We also provide the following services:

- Seathane polyurethane coating of steel buoys
- In-place polyurethane casting
- Floatation device & fendering design
- Buoy mooring design

Mailing & Shipping Address: **30150 Eden Church Road**
Denham Springs, LA 70726
U.S.A.

Telephone: 225\664-9936 **Fax: 225\664-9938**
Web Site: www.utibuoys.com **E-mail: uti@utibuoys.com**

2/13/2001 printing