



SD SERIES MOORING BUOYS

Buoys in this series are designed for mooring small to medium size craft. Each **SD** mooring buoy has a galvanized steel swivel made into the lower closed 'U' hook.

- The **SD** series is made of closed cell, crosslinked polyethylene foam covered with a tough Seathane[®] polyurethane skin.
- Steel components of these buoys are hot dipped galvanized steel. Stainless steel is optional at an additional cost.
- The **SD** series buoys are not internally ballasted. They depend on the weight of the mooring to maintain a proper attitude.

Model No.	Diameter	Height	Rod Dia.	Weight	Net* Buoyancy	Maximum Through Pull
SD-04	22"	26"	5/8"	72 lbs.	285 lbs.	7,200 lbs.
SD-05	24"	28-1/2"	5/8"	80 lbs.	465 lbs.	7,200 lbs.
SD-06	26"	29"	3/4"	87 lbs.	555 lbs.	10,700 lbs.
SD-08	28"	34"	7/8"	118 lbs.	755 lbs.	14,900 lbs.
SD-10	30"	36"	1"	140 lbs.	915 lbs.	19,600 lbs.
SD-12	32"	38"	1-1/8"	157 lbs.	947 lbs.	24,600 lbs.
SD-15	36"	38"	1-1/4"	195 lbs.	1,200 lbs.	34,500 lbs.

* Net Buoyancy is in fresh water.

An underwater weight of 20% to 40% of the buoy's net buoyancy should be provided by the mooring.

These buoys are not intended for use in areas where ice may crust in excess of 2".

Seathane[®] is a trademark of Urethane Technologies, Inc.

