

STUD LINK ANCHOR CHAIN

Stud link anchor chain differs from standard chain by the reinforcing cross member at the center of each link. This cross member allows the chain to endure a greater pull force than standard chain without deforming.



CHAIN SIZE	WEIGHT IN POUNDS PER LINEAL FOOT	
	IN AIR	UNDER SEAWATER
5/8"	4.06	3.53
3/4"	5.33	4.64
13/16"	6.33	5.51
7/8"	7.33	6.38
15/16"	8.44	7.34
1"	9.56	8.31
1- 1/16"	10.78	9.37
1- 1/8"	12.00	10.43
1- 3/16"	13.56	11.79
1- 1/4"	15.00	13.04
1- 5/16"	16.56	14.40
1- 3/8"	18.11	15.75
1- 7/16"	19.78	17.20
1- 1/2"	21.56	18.74
1- 9/16"	23.22	20.19
1- 5/8"	24.89	21.64
1-11/16"	26.78	23.28
1- 3/4"	28.78	25.02
1-13/16"	31.00	26.96
1- 7/8"	33.11	28.79
1-15/16"	35.33	30.72
2"	37.33	32.46
2- 1/16"	39.67	34.49
2- 1/8"	42.11	36.62
2- 3/16"	44.67	38.84
2- 1/4"	47.22	41.06
2- 5/16"	49.89	43.38
2- 3/8"	52.56	45.70
2- 7/16"	55.11	47.92
2- 1/2"	58.56	50.92
2- 9/16"	61.56	53.53
2- 5/8"	64.67	56.23
2-11/16"	67.89	59.03
2- 3/4"	71.22	61.93
2-13/16"	74.56	64.83
2- 7/8"	78.00	67.82
2-15/16"	81.44	70.82
3"	85.00	73.91
3- 1/16"	88.67	77.10
3- 1/8"	92.44	80.38
3- 3/16"	96.22	83.67
3- 1/4"	100.11	87.05
3- 5/16"	104.00	90.43
3- 3/8"	108.11	94.01
3- 7/16"	112.22	97.58
3- 1/2"	116.67	101.45
3- 5/8"	125.56	109.18
3- 3/4"	133.33	115.94
3- 7/8"	143.33	124.64
4"	152.22	132.36